

Bruck Norcote Bulk/Bulk Plus

Utilización final: Magazines, catalogues, supplements, direct mail, inserts/flyers

Propiedad	ISO						
			Bulk	Bulk	Bulk	Bulk	Bulk Plus
Gramaje	(ISO 536)	(g/m ²)	54	57	60	70	80
Espesor	(ISO 534)	(µm)	65	69	72	84	96
Volumen Específico	(ISO 534)	(cm ³ /g)	1.2	1.2	1.2	1.2	1.2
Blancura D 65	(ISO 2470)	(%)	86	86	86	86	95
Blancura CIE	(ISO 11475)	(%)	100	102	102	102	120
Tonalidad L D 65	(ISO 5631-2)	(D65/10°)	91	91	92	92	94
Tonalidad A D 65	(ISO 5631-2)	(D65/10°)	0.2	0.2	0.2	0.2	1.2
Tonalidad B D 65	(ISO 5631-2)	(D65/10°)	-4.1	-4.3	-4.6	-4.6	-7.5
Opacidad	(ISO 2471)	(%)	91	93	94	95	96
Brillo (Lehman)	(ISO 8254-1) (Tappi T480)	(%)	16	20	20	20	20

Pre-press datos	ISO						
CIE L*-value**	13655, M1	D50/2°	91.5	91.5	92	92	93
CIE a*-value**	13655, M1	D50/2°	-0.3	-0.3	-0.3	-0.3	0.5
CIE b*-value**	13655, M1	D50/2°	-1.0	-1.0	-1.0	-1.0	-3

Recomendada ICC-Perfil: Recommended ICC-Profile: FOGRA 45L (PSO LWC Improved / ISO 12647-2:2004)

FAMILIA DE PRODUCTOS:
Norcote

SISTEMA DE IMPRESIÓN:
Heat set web offset

*Last Updated:
December 2020*

ACABADO:
Matt

PRODUCTOR:
Bruck

Norske Skog Bruck
tiene la certificación:

Paper Profile
PEFC (ENG)
FSC
EU Ecolabel
ISO 9001:2008
ISO 14001:2004
ISO 18001: 2007
PEFC (DE)