

Bruck Norcote Bulk/Bulk Plus

Anwendung: Magazines, catalogues, supplements, direct mail, inserts/flyers

Grundlegende Merkmale	ISO		Bulk				
			Bulk	Bulk	Bulk	Bulk	Bulk Plus
Flächenbezogene Masse	(ISO 536)	(g/m ²)	54	57	60	70	80
Dicke	(ISO 534)	(µm)	65	69	72	84	96
Spez. Volumen	(ISO 534)	(cm ³ /g)	1.2	1.2	1.2	1.2	1.2
Weisse, D65/10 (UV)	(ISO 2470)	(%)	86	86	86	86	95
Weisse CIE	(ISO 11475)	(%)	100	102	102	102	120
L*	(ISO 5631-2)	(D65/10°)	91	91	92	92	94
a*	(ISO 5631-2)	(D65/10°)	0.2	0.2	0.2	0.2	1.2
b*	(ISO 5631-2)	(D65/10°)	-4.1	-4.3	-4.6	-4.6	-7.5
Opazität	(ISO 2471)	(%)	91	93	94	95	96
Glanz (Lehmann)	(ISO 8254-1) (Tappi T480)	(%)	16	20	20	20	20

Pre-press Daten	ISO		Bulk				
CIE L*-value**	13655, M1	D50/2°	91.5	91.5	92	92	93
CIE a*-value**	13655, M1	D50/2°	-0.3	-0.3	-0.3	-0.3	0.5
CIE b*-value**	13655, M1	D50/2°	-1.0	-1.0	-1.0	-1.0	-3

Empfohlenes ICC-Profil: Recommended ICC-Profil: FOGRA 45L (PSO LWC Improved / ISO 12647-2:2004)

PRODUKTFAMILIE:
Norcote

OBERFLÄCHE:
Matt

DRUCKVERFAHREN:
Heat set web offset

HERSTELLER:
Bruck

*Last Updated:
December 2020*

Norske Skog Bruck ist
zertifiziert nach:

Paper Profile
PEFC (ENG)
FSC
EU Ecolabel
ISO 9001:2008
ISO 14001:2004
ISO 18001: 2007
PEFC (DE)