

# Bruck Norcote Satin

**Anwendung:** Magazines, catalogues, supplements, direct mail, inserts/flyers

Grundlegende Merkmale	ISO		54*	57*	60*	65*	70*	80*
Flächenbezogene Masse	(ISO 536)	(g/m <sup>2</sup> )	54*	57*	60*	65*	70*	80*
Dicke	(ISO 534)	(µm)	54	57	59	64	67	75
Spez. Volumen	(ISO 534)	(cm <sup>3</sup> /g)	1.00	1.00	0.98	0.98	0.96	0.94
Weisse, D65/10 (UV)	(ISO 2470)	(%)	76	76	76	76	76	76
Weisse CIE	(ISO 11475)	(%)	73	73	73	73	73	73
L*	(ISO 5631-2)	(D65/10°)	90	91	91	91	91	91
a*	(ISO 5631-2)	(D65/10°)	-0.2	-0.2	-0.2	-0.2	-0.2	-0.2
b*	(ISO 5631-2)	(D65/10°)	1.2	1.2	1.2	1.2	1.2	1.2
Opazität	(ISO 2471)	(%)	91	92	93	94	94	95
Glanz (Lehmann)	(ISO 8254-1) (Tappi T480)	(%)	20	25	28	33	35	36
Glätte	(ISO 8791-4)	(µm)	2.5	2.5	2.5	2.5	2.5	2.5

Pre-press Daten	ISO		91	91	91	91	91	91
CIE L*-value**	13655, M1	D50/2°	91	91	91	91	91	91
CIE a*-value**	13655, M1	D50/2°	0	0	0	0	0	0
CIE b*-value**	13655, M1	D50/2°	2.5	2.5	2.5	2.5	2.5	2.5

**Empfohlenes ICC-Profil:** FOGRA 46L (PSO LWC Standard / ISO 12647-2:2013)

PRODUKTFAMILIE:  
Norcote

OBERFLÄCHE:  
Silk

DRUCKVERFAHREN:  
Heat set web offset

HERSTELLER:  
Bruck

*Last Updated:  
January 2019*

Norske Skog Bruck ist  
zertifiziert nach:

Paper Profile  
PEFC (ENG)  
FSC  
EU Ecolabel  
ISO 9001:2008  
ISO 14001:2004  
ISO 18001: 2007  
PEFC (DE)