

## Bruck NorX

**End use:** Newspapers, direct mail, free-sheets, directories, supplements, inserts/flyers, magazines, books

The NorX range offers higher brightness properties and an enhanced printed image compared to newsprint. These products are especially well suited to heat set web offset.

The paper achieves its higher performance characteristics through the use of modern, twin wire paper machines and enhanced thermomechanical pulping processes.

Basic properties	ISO					
Basis Weight	(ISO 536)	(g/m <sup>2</sup> )	40*	42.5*	45	48,8
Thickness	(ISO 534)	(µm)	50	53	56	59
Density	(ISO 534)	(kg/m <sup>3</sup> )	800	800	800	820
Bulk	(ISO 534)	(cm <sup>3</sup> /g)	1.25	1.25	1.25	1.20
Roughness	(ISO 8791-4)	(µm)	85	85	85	85
Brightness D65	(ISO 2470)	(%)	59	59	59	59
L-value D65	(ISO 5631-2)	(D65/10°)	83	83	83	83
a-value D65	(ISO 5631-2)	(D65/10°)	-0,3	-0,3	-0,3	-0,3
b-value D65	(ISO 5631-2)	(D65/10°)	3,0	3,0	3,0	3,0
Opacity.	(ISO 2471)	(%)	93	94	94	95

PRODUCT FAMILY:  
Norbright, Norstar,  
NorX

PRINTING METHOD:  
Heat set web offset

*Last Updated:  
September 2017*

FINISH:  
Matt

PRODUCER:  
Bruck

Norske Skog Bruck is  
certified according to:

PEFC  
FSC  
EU Ecolabel  
ISO 9001  
ISO 14001  
ISO 45001  
Paper Profile

## We use cookies

Norske Skog ASA This website uses cookies to track your behavior and to improve your experience on the site. [norskeskog.com](https://www.norskeskog.com)  
You can always delete saved cookies by visiting the advanced settings of your browser. [Read more about our cookies.](#)

Do not accept cookies

Only accept functional cookies

Accept all cookies