

## Bruck NorX

**Utilización final:** Newspapers, direct mail, free-sheets, directories, supplements, inserts/flyers, magazines, books

The NorX range offers higher brightness properties and an enhanced printed image compared to newsprint. These products are especially well suited to heat set web offset.

The paper achieves its higher performance characteristics through the use of modern, twin wire paper machines and enhanced thermomechanical pulping processes.

Propiedad	ISO					
Gramaje	(ISO 536)	(g/m <sup>2</sup> )	40*	42.5*	45	48,8
Espesor	(ISO 534)	(µm)	50	53	56	59
Densidad	(ISO 534)	(kg/m <sup>3</sup> )	800	800	800	820
Volumen Específico	(ISO 534)	(cm <sup>3</sup> /g)	1.25	1.25	1.25	1.20
Rugosidad	(ISO 8791-4)	(µm)	85	85	85	85
Blancura D 65	(ISO 2470)	(%)	59	59	59	59
Tonalidad L D 65	(ISO 5631-2)	(D65/10°)	83	83	83	83
Tonalidad A D 65	(ISO 5631-2)	(D65/10°)	-0,3	-0,3	-0.3	-0.3
Tonalidad B D 65	(ISO 5631-2)	(D65/10°)	3,0	3,0	3.0	3.0
Opacidad	(ISO 2471)	(%)	93	94	94	95

FAMILIA DE PRODUCTOS:  
Norbright, Norstar, NorX

SISTEMA DE IMPRESIÓN:  
Heat set web offset

*Last Updated:  
September 2017*

ACABADO:  
Matt

PRODUCTOR:  
Bruck

Norske Skog Bruck  
tiene la certificación:

PEFC  
FSC  
EU Ecolabel  
ISO 9001  
ISO 14001  
ISO 45001  
Paper Profile