

Bruck NorX

Anwendung: Newspapers, direct mail, free-sheets, directories, supplements, inserts/flyers, magazines, books

The NorX range offers higher brightness properties and an enhanced printed image compared to newsprint. These products are especially well suited to heat set web offset.

The paper achieves its higher performance characteristics through the use of modern, twin wire paper machines and enhanced thermomechanical pulping processes.

Grundlegende Merkmale	ISO					
Flächenbezogene Masse	(ISO 536)	(g/m ²)	40*	42.5*	45	48,8
Dicke	(ISO 534)	(µm)	50	53	56	59
Blattdichte	(ISO 534)	(kg/m ³)	800	800	800	820
Spez. Volumen	(ISO 534)	(cm ³ /g)	1.25	1.25	1.25	1.20
Rauhigkeit (PPS 1MPa)	(ISO 8791-4)	(µm)	85	85	85	85
Weisse, D65/10 (UV)	(ISO 2470)	(%)	59	59	59	59
L*	(ISO 5631-2)	(D65/10°)	83	83	83	83
a*	(ISO 5631-2)	(D65/10°)	-0,3	-0,3	-0,3	-0,3
b*	(ISO 5631-2)	(D65/10°)	3,0	3,0	3,0	3,0
Opazität	(ISO 2471)	(%)	93	94	94	95

PRODUKTFAMILIE:
Norbright, Norstar,
NorX

DRUCKVERFAHREN:
Heat set web offset

*Last Updated:
September 2017*

OBERFLÄCHE:
Matt

HERSTELLER:
Bruck

Norske Skog Bruck ist
zertifiziert nach:

PEFC
FSC
EU Ecolabel
ISO 9001
ISO 14001
ISO 45001
Paper Profile