

Golbey NorX Plus

End use: Newspapers, direct mail, free-sheets, directories, supplements, inserts/flyers, magazines, books

Furnish: Recycled and virgin fibres Reel width: From 300 to 2860 mm Reel diameter: Up 1500 mm Core: 76 and 150 mm

| Basic properties | ISO | | | | | | | | |
|------------------|---------------|----------------------|------|------|------|------|------|------|------|
| Basis Weight | (ISO 536) | (g/m ²) | 34 | 36 | 38 | 40 | 42 | 45 | 48.8 |
| Thickness | (ISO 534) | (µm) | 41 | 43 | 46 | 48 | 50 | 54 | 59 |
| Density | (ISO 534) | (kg/m ³) | 830 | 830 | 830 | 830 | 830 | 830 | 830 |
| Bulk | (ISO 534) | (cm ³ /g) | 1.2 | 1.2 | 1,2 | 1,2 | 1,2 | 1,2 | 1.2 |
| Roughness | (ISO 8791-4) | (µm) | 2.5 | 2,5 | 2,5 | 2,5 | 2,5 | 2,5 | 2.5 |
| Brightness D65 | (ISO 2470) | (%) | 58 | 58 | 58 | 58 | 58 | 58 | 58 |
| L-value D65 | (ISO 5631-2) | (D65/10°) | 82.0 | 82,0 | 82,0 | 82,0 | 82,0 | 82,0 | 82.0 |
| a-value D65 | (ISO 5631-2) | (D65/10°) | -0.8 | -0,8 | -0,8 | -0,8 | -0,8 | -0,8 | -0.8 |
| b-value D65 | (ISO 5631-2) | (D65/10°) | 5.2 | 5,2 | 5,2 | 5,2 | 5,2 | 5,2 | 5.2 |
| Opacity. | (ISO 2471) | (%) | 90 | 91 | 92 | 92,5 | 93,5 | 94,5 | 96.5 |

| Pre-press data | ISO |
|----------------|-----|
| CIE L*-value** | . |
| CIE a*-value** | . |
| CIE b*-value** | . |

Recommended ICC-Profile: Fogra 42L.txt (PSO_SNP_paper_eci.icc / ISO12647-3:2015)

PRODUCT FAMILY:
NorX, Nornews

FINISH:
Matt

PRINTING METHOD:
Heat set web offset

PRODUCER:
Golbey

*Last Updated:
July 2020*

Norske Skog Golbey is
certified according to:

ISO 14001
EU Ecolabel
PEFC
FSC
ISO 9001
Paper Profile 2020
Blue Angel NorX Plus
ISO 50001