

Golbey NorX Plus

End use: Newspapers, direct mail, free-sheets, directories, supplements, inserts/flyers, magazines, books

Furnish: Recycled and virgin fibres Reel width: From 300 to 2860 mm Reel diameter: Up 1500 mm Core: 76 and 150 mm

| Basic properties | ISO | | | | | | | | |
|------------------|---------------|----------------------|------|------|------|------|------|------|------|
| Basis Weight | (ISO 536) | (g/m ²) | 34 | 36 | 38 | 40 | 42 | 45 | 48.8 |
| Thickness | (ISO 534) | (µm) | 41 | 43 | 46 | 48 | 50 | 54 | 59 |
| Density | (ISO 534) | (kg/m ³) | 830 | 830 | 830 | 830 | 830 | 830 | 830 |
| Bulk | (ISO 534) | (cm ³ /g) | 1.2 | 1.2 | 1,2 | 1,2 | 1,2 | 1,2 | 1.2 |
| Roughness | (ISO 8791-4) | (µm) | 2.5 | 2,5 | 2,5 | 2,5 | 2,5 | 2,5 | 2.5 |
| Brightness D65 | (ISO 2470) | (%) | 58 | 58 | 58 | 58 | 58 | 58 | 58 |
| L-value D65 | (ISO 5631-2) | (D65/10°) | 82.0 | 82,0 | 82,0 | 82,0 | 82,0 | 82,0 | 82.0 |
| a-value D65 | (ISO 5631-2) | (D65/10°) | -0.8 | -0,8 | -0,8 | -0,8 | -0,8 | -0,8 | -0.8 |
| b-value D65 | (ISO 5631-2) | (D65/10°) | 5.2 | 5,2 | 5,2 | 5,2 | 5,2 | 5,2 | 5.2 |
| Opacity. | (ISO 2471) | (%) | 90 | 91 | 92 | 92,5 | 93,5 | 94,5 | 96.5 |

| Pre-press data | ISO |
|----------------|-----|
| CIE L*-value** | . |
| CIE a*-value** | . |
| CIE b*-value** | . |

Recommended ICC-Profile: Fogra 42L.txt (PSO_SNP_paper_eci.icc / ISO12647-3:2015)

PRODUCT FAMILY:
NorX, Nornews

FINISH:
Matt

PRINTING METHOD:
Heat set web offset

PRODUCER:
Golbey

*Last Updated:
July 2020*

Norske Skog Golbey is certified according to:

ISO 14001
EU Ecolabel
PEFC
FSC
ISO 9001
Paper Profile 2020
Blue Angel NorX Plus
ISO 50001

We use cookies

Norske Skog ASA This website uses cookies to track your behavior and to improve your experience on the site. [norskeskog.com](https://www.norskeskog.com)
You can always delete saved cookies by visiting the advanced settings of your browser. [Read more about our cookies.](#)

Do not accept cookies

Only accept functional cookies

Accept all cookies