

Golbey NorX Plus

Anwendung: Newspapers, direct mail, free-sheets, directories, supplements, inserts/flyers, magazines, books

Furnish: Recycled and virgin fibres Reel width: From 300 to 2860 mm Reel diameter: Up 1500 mm Core: 76 and 150 mm

Grundlegende Merkmale	ISO								
Flächenbezogene Masse	(ISO 536)	(g/m ²)	34	36	38	40	42	45	48.8
Dicke	(ISO 534)	(µm)	41	43	46	48	50	54	59
Blattdichte	(ISO 534)	(kg/m ³)	830	830	830	830	830	830	830
Spez. Volumen	(ISO 534)	(cm ³ /g)	1.2	1.2	1,2	1,2	1,2	1,2	1.2
Rauhigkeit (PPS 1MPa)	(ISO 8791-4)	(µm)	2.5	2,5	2,5	2,5	2,5	2,5	2.5
Weisse, D65/10 (UV)	(ISO 2470)	(%)	58	58	58	58	58	58	58
L*	(ISO 5631-2)	(D65/10°)	82.0	82,0	82,0	82,0	82,0	82,0	82.0
a*	(ISO 5631-2)	(D65/10°)	-0.8	-0,8	-0,8	-0,8	-0,8	-0,8	-0.8
b*	(ISO 5631-2)	(D65/10°)	5.2	5,2	5,2	5,2	5,2	5,2	5.2
Opazität	(ISO 2471)	(%)	90	91	92	92,5	93,5	94,5	96.5

Pre-press Daten	ISO
CIE L*-value**	.
CIE a*-value**	.
CIE b*-value**	.
Empfohlenes ICC-Profil: Fogra 42L.txt (PSO_SNP_paper_eci.icc / ISO12647-3:2015)	

PRODUKTFAMILIE:
NorX, Nornews

OBERFLÄCHE:
Matt

DRUCKVERFAHREN:
Heat set web offset

HERSTELLER:
Golbey

*Last Updated:
July 2020*

Norske Skog Golbey ist
zertifiziert nach:

ISO 14001
EU Ecolabel
PEFC
FSC
ISO 9001
Paper Profile 2020
Blue Angel NorX Plus
ISO 50001