

# Golbey NorX

**Utilisation finale:** Newspapers, direct mail, free-sheets, directories, supplements, inserts/flyers, magazines, books

The NorX range offers higher brightness properties and an enhanced printed image compared to newsprint. These products are especially well suited to heat set web offset.

The paper achieves its higher performance characteristics through the use of modern, twin wire paper machines and enhanced thermomechanical pulping processes.

Caractéristiques de base	ISO								
Grammage	(ISO 536)	(g/m <sup>2</sup> )	34	36	38	40	42	45	48.8
Epaisseur	(ISO 534)	(µm)	44	47	49	52	54	58	63
Densité	(ISO 534)	(kg/m <sup>3</sup> )	770	770	770	770	770	770	770
Main	(ISO 534)	(cm <sup>3</sup> /g)	1.3	1,3	1,3	1,3	1,3	1,3	1.3
Rugosité	(ISO 8791-4)	(µm)	3.2	3,2	3,2	3,2	3,2	3,2	3.2
Blancheur D65	(ISO 2470)	(%)	58	58	58	58	58	58	58
Luminance	(ISO 5631-2)	(D65/10°)	82.3	82,3	82,3	82,3	82,3	82,3	82.3
Valeur A	(ISO 5631-2)	(D65/10°)	-0.8	-0,8	-0,8	-0,8	-0,8	-0,8	-0.8
Valeur B	(ISO 5631-2)	(D65/10°)	5.2	5,2	5,2	5,2	5,2	5,2	5.2
Opacité	(ISO 2471)	(%)	90	91	92	92,5	93,5	94,5	95.5

Pre-press données	ISO
CIE L*-valeur**	.
CIE a*-valeur**	.
CIE b*-valeur**	.

**Recommandé ICC-Profil:** Fogra 42L.txt (PSO\_SNP\_paper\_eci.icc / ISO12647-3:2015)

FAMILLE DE  
PRODUITS:  
Norbright, Norstar,  
NorX

MÉTHODE  
D'IMPRESSIION:  
Heat set web offset

*Last Updated:  
November 2020*

SURFACE:  
Matt

PRODUCTEUR:  
Golbey

Norske Skog Golbey  
est certifié selon:

ISO 14001  
PEFC  
FSC  
Blue Angel NorX  
Paper Profile 2020  
EU Ecolabel  
ISO 9001  
ISO 50001