

Golbey NorX

Anwendung: Newspapers, direct mail, free-sheets, directories, supplements, inserts/flyers, magazines, books

The NorX range offers higher brightness properties and an enhanced printed image compared to newsprint. These products are especially well suited to heat set web offset.

The paper achieves its higher performance characteristics through the use of modern, twin wire paper machines and enhanced thermomechanical pulping processes.

Grundlegende Merkmale	ISO								
Flächenbezogene Masse	(ISO 536)	(g/m ²)	34	36	38	40	42	45	48.8
Dicke	(ISO 534)	(µm)	44	47	49	52	54	58	63
Blattdichte	(ISO 534)	(kg/m ³)	770	770	770	770	770	770	770
Spez. Volumen	(ISO 534)	(cm ³ /g)	1.3	1,3	1,3	1,3	1,3	1,3	1.3
Rauhigkeit (PPS 1MPa)	(ISO 8791-4)	(µm)	3.2	3,2	3,2	3,2	3,2	3,2	3.2
Weisse, D65/10 (UV)	(ISO 2470)	(%)	58	58	58	58	58	58	58
L*	(ISO 5631-2)	(D65/10°)	82.3	82,3	82,3	82,3	82,3	82,3	82.3
a*	(ISO 5631-2)	(D65/10°)	-0.8	-0,8	-0,8	-0,8	-0,8	-0,8	-0.8
b*	(ISO 5631-2)	(D65/10°)	5.2	5,2	5,2	5,2	5,2	5,2	5.2
Opazität	(ISO 2471)	(%)	90	91	92	92,5	93,5	94,5	95.5

Pre-press Daten	ISO
CIE L*-value**	.
CIE a*-value**	.
CIE b*-value**	.

Empfohlenes ICC-Profil: Fogra 42L.txt (PSO_SNP_paper_eci.icc / ISO12647-3:2015)

PRODUKTFAMILIE:
Norbright, Norstar,
NorX

OBERFLÄCHE:
Matt

DRUCKVERFAHREN:
Heat set web offset

HERSTELLER:
Golbey

*Last Updated:
November 2020*

Norske Skog Golbey ist
zertifiziert nach:

ISO 14001
PEFC
FSC
Blue Angel NorX
Paper Profile 2020
EU Ecolabel
ISO 9001
ISO 50001