

Skogn Norbright 68

End use: Newspapers, direct mail, free-sheets, directories, supplements, inserts/flyers, magazines, books

The Norbright range offers higher brightness properties and an enhanced printed image compared to newsprint. These products are especially well suited to cold set web offset, although they can also be used for heat set.

The paper achieves its higher performance characteristics through the use of modern, twin wire paper machines and enhanced thermomechanical pulping processes.

Basic properties	ISO					
Basis Weight	(ISO 536)	(g/m ²)	45*	48.8	52	55
Thickness	(ISO 534)	(µm)	66	70	74	79
Density	(ISO 534)	(kg/m ³)	700	700	700	700
Bulk	(ISO 534)	(cm ³ /g)	1.5	1.4	1.4	1.4
Brightness D65	(ISO 2470)	(%)	68	68	68	68
L-value D65	(ISO 5631-2)	(D65/10°)	87	87	87	87
a-value D65	(ISO 5631-2)	(D65/10°)	-0.3	-0.3	-0.3	-0.3
b-value D65	(ISO 5631-2)	(D65/10°)	2.0	2.0	2.0	2.0
Opacity	(ISO 2471)	(%)	91.0	92.0	93.0	93.5

PRODUCT FAMILY:
Norbright 62/65/
Norbright Plus

FINISH:
Matt

Norske Skog Skogn is certified according to:

PRINTING METHOD:
Cold set web offset /
(Heat set web offset)

PRODUCER:
Skogn

ISO 9001
ISO 14001
ISO 50001
PEFC Chain of Custody
FSC Chain of Custody
EU Timber Regulation
EU Ecolabel
Paper Profile

*Last Updated:
October 2020*

We use cookies

Norske Skog ASA This website uses cookies to track your behavior and to improve your experience on the site. [norskeskog.com](https://www.norskeskog.com)
You can always delete saved cookies by visiting the advanced settings of your browser. [Read more about our cookies.](#)

Do not accept cookies

Only accept functional cookies

Accept all cookies