

Saugbrugs NorSC Value

Utilisation finale: Magazines, inserts, catalogues, direct mail and door drop.

Caractéristiques de base	ISO					
Grammage	(ISO 536)	(g/m ²)	42*	45	47.4	52
Epaisseur	(ISO 534)	(µm)	42	45	47.4	52
Densité	(ISO 534)	(kg/m ³)	1000	1000	1000	1000
Main	(ISO 534)	(cm ³ /g)	1.00	1.00	1.00	1.00
Blancheur D65	(ISO 2470)	(%)	65	65	65	65
Blancheur CIE	(ISO 11475)	(%)	45	45	45	45
Luminance	(ISO 5631-2)	(D65/10°)	86.5	86.5	86.5	86.5
Valeur A	(ISO 5631-2)	(D65/10°)	-1.5	-1.5	-1.5	-1.5
Valeur B	(ISO 5631-2)	(D65/10°)	5.5	5.5	5.5	5.5
Opacité	(ISO 2471)	(%)	89	91	92	94
Brillance Hunter	(ISO 8254-1)	(%)	35	35	35	35
Lissé (Rugosité) PPS 10	(ISO 8791-4)	(µm)	1.8	1.7	1.7	1.6

FAMILLE DE
PRODUITS:

SURFACE:
SC

Norske Skog
Saugbrugs est certifié
selon:

MÉTHODE
D'IMPRESSON:
Heatset & Rotogravure
Characterization data:
Fogra 40

PRODUCTEUR:
Saugbrugs

EU Ecolabel
PEFC
FSC
EU Timber Regulation
ISO 5001:2011
ISO 9001:2015
ISO 14001:2015
Paper Profile
EU Timber Regulation

*Last Updated:
May 2019*