

Saugbrugs NorSC Value

Anwendung: Magazines, inserts, catalogues, direct mail and door drop.

Product Family: SC

Grundlegende Merkmale	ISO					
Flächenbezogene Masse	(ISO 536)	(g/m ²)	42	45	47.4	52
Dicke	(ISO 534)	(µm)	42	45	47.4	52
Blattdichte	(ISO 534)	(kg/m ³)	1000	1000	1000	1000
Spez. Volumen	(ISO 534)	(cm ³ /g)	1.00	1.00	1.00	1.00
Weisse, D65/10 (UV)	(ISO 2470)	(%)	65	65	65	65
Weisse CIE	(ISO 11475)	(%)	45	45	45	45
L*	(ISO 5631-2)	(D65/10°)	86.5	86.5	86.5	86.5
a*	(ISO 5631-2)	(D65/10°)	-1.5	-1.5	-1.5	-1.5
b*	(ISO 5631-2)	(D65/10°)	5.5	5.5	5.5	5.5
Opazität	(ISO 2471)	(%)	89	91	92	94
Glanz (Hunter)	(ISO 8254-1)	(%)	35	35	35	35
Glätte	(ISO 8791-4)	(µm)	1.8	1.7	1.7	1.6

PRODUKTFAMILIE:
Nor

OBERFLÄCHE:
Gloss

DRUCKVERFAHREN:
Heatset & Rotogravure

HERSTELLER:
Saugbrugs

CHARACTERIZATION
DATA:
Fogra 40

*Last Updated:
May 2019*

Norske Skog
Saugbrugs ist
zertifiziert nach:

EU Ecolabel
PEFC
FSC
EU Timber Regulation
ISO 5001:2018
ISO 9001:2015
ISO 14001:2015
Paper Profile
Norske Skog Saugbrugs -
Carbon Footprint