

Skogn Nornews

End use: Newspapers, free-sheets, directories, supplements,

inserts/flyers



Basic properties	ISO				
Basis Weight	(ISO 536)	(g/m²)	40	42.5	45
Thickness	(ISO 534)	(µm)	56-62	60-63	61-68
Density	(ISO 534)	(kg/m3)	640-700	640-700	640-700
Bulk	(ISO 534)	(cm3/g)	1.45-1.55	1.45-1.55	1.45-1.55
Brightness D65	(ISO 2470)	(%)	58	58	58
L-value D65	(ISO 5631-2)	(D65/10°)	83.4	83.4	83.4
a-value D65	(ISO 5631-2)	(D65/10°)	-0.3	-0.3	-0.3
b-value D65	(ISO 5631-2)	(D65/10°)	5.0	5.0	5.0
Opacity.	(ISO 2471)	(%)	91.5-92.5	92.5-94	93.5-94.5

PRODUCT FAMILY: Nornews, Nornews

Flexo

FINISH: Matt

PRINTING METHOD:

Cold set web offset

Last Updated:

August 2018

): S.

PRODUCER: Skogn Norske Skog Skogn is certified according to:

ISO 9001:2008 ISO 14001:2004 ISO 50001:2011 PEFC Chain of Custody FSC Chain of Custody EU Timber Regulation Paper Profile

Phone: +47 22 51 20 20

Main fax: +47 22 51 20 21