

# Saugbrugs Nor Opaq Plus

**Anwendung:** Magazines, inserts, catalogues, direct mail and door drop.

**Product Family:** UMI

Grundlegende Merkmale	ISO								
Flächenbezogene Masse	(ISO 536)	(g/m <sup>2</sup> )	42*	45	47,4	51	54	57	60
Dicke	(ISO 534)	(µm)	53	55	55	57	58	60	62
Blattdichte	(ISO 534)	(kg/m <sup>3</sup> )	800	840	860	900	920	940	950
Spez. Volumen	(ISO 534)	(cm <sup>3</sup> /g)	1.2	1.15	1.15	1.15	1.1	1.1	1.1
Weisse, D65/10 (UV)	(ISO 2470)	(%)	76	80	80	80	80	80	80
Weisse CIE	(ISO 11475)	(%)	74	75	75	75	75	75	75
L*	(ISO 5631-2)	(D65/10°)	90	90	90	90	90	90	90
a*	(ISO 5631-2)	(D65/10°)	0.2	0.2	0.2	0.2	0.2	0.2	0.2
b*	(ISO 5631-2)	(D65/10°)	-0.5	-0.5	-0.5	-0.5	-0.5	-0.5	-0.5
Opazität	(ISO 2471)	(%)	91	92	93	94	95	96	97
Glanz (Hunter)	(ISO 8254-1)	(%)	20-25	20-25	20-25	20-25	20-25	20-25	20-25
Glätte	(ISO 8791-4)	(µm)	1.7	1.7	1.7	1.7	1.7	1.7	1.7

PRODUKTFAMILIE:  
Nor

OBERFLÄCHE:  
Silk

DRUCKVERFAHREN:  
Heatset & Rotogravure

HERSTELLER:  
Saugbrugs

CHARACTERIZATION  
DATA:

Heatset: Fogra 41L  
Gravure: ICC Paper  
profile -  
PSR\_MF\_V2\_M1.icc

*Last Updated:  
October 2020*

Norske Skog  
Saugbrugs ist  
zertifiziert nach:

Paper Profile  
PEFC  
FSC  
EU Timber Regulation  
ISO 50001: 2018  
ISO 9001: 2015  
ISO 14001: 2015  
EU Ecolabel  
Norske Skog Saugbrugs -  
Carbon Footprint