

# Boyer Vantage Satin

**End use:** Magazines, catalogues, supplements, direct mail, inserts/flyers

100% plantation softwood fibre - All fibre is sourced from well managed plantation forests and other controlled sources - No native timber used - Elemental chlorine free

Basic properties	ISO				
Basis Weight	(ISO 536)	(g/m <sup>2</sup> )	65	70	75
Thickness	(ISO 534)	(µm)	73	78	84
Bulk	(ISO 534)	(cm <sup>3</sup> /g)	1.1	1.1	1.1
Brightness D65	(ISO 2470)	(%)	85	85	85
L-value D65	(ISO 5631-2)	(D65/10°)	90	90	90
a-value D65	(ISO 5631-2 )	(D65/10°)	0.6	0.6	0.6
b-value D65	(ISO 5631-2)	(D65/10°)	-5.5	-5.5	-5.5
Opacity.	(ISO 2471)	(%)	94	94	95
Gloss Hunter	(ISO 8254-1)	(%)	28	28	28

PRODUCT FAMILY:  
Vantage

FINISH:  
Satin

PRINTING METHOD:

PRODUCER:  
Boyer

*Last Updated:  
29 September 2016*

Norske Skog Boyer is  
certified according to:

Paper Profile Document  
AS/ANZ ISO 14001:2015  
FSC Forest Management  
FSC Chain of Custody  
PEFC Chain of Custody