

Boyer Vantage Satin

Anwendung: Magazines, catalogues, supplements, direct mail, inserts/flyers

100% plantation softwood fibre - All fibre is sourced from well managed plantation forests and other controlled sources - No native timber used - Elemental chlorine free

Grundlegende Merkmale	ISO				
Flächenbezogene Masse	(ISO 536)	(g/m ²)	65	70	75
Dicke	(ISO 534)	(µm)	73	78	84
Spez. Volumen	(ISO 534)	(cm ³ /g)	1.1	1.1	1.1
Weisse, D65/10 (UV)	(ISO 2470)	(%)	85	85	85
L*	(ISO 5631-2)	(D65/10°)	90	90	90
a*	(ISO 5631-2)	(D65/10°)	0.6	0.6	0.6
b*	(ISO 5631-2)	(D65/10°)	-5.5	-5.5	-5.5
Opazität	(ISO 2471)	(%)	94	94	95
Glanz (Hunter)	(ISO 8254-1)	(%)	28	28	28

PRODUKTFAMILIE:
Vantage

OBERFLÄCHE:
Satin

DRUCKVERFAHREN:

HERSTELLER:
Boyer

*Last Updated:
29 September 2016*

Norske Skog Boyer ist
zertifiziert nach:

Paper Profile Document
AS/ANZ ISO 14001:2015
FSC Forest Management
FSC Chain of Custody
PEFC Chain of Custody