

# Boyer Vantage Super

**End use:** Magazines, catalogues, supplements, direct mail, inserts/flyers

100% plantation softwood fibre - All fibre is sourced from well managed plantation forests and other controlled sources - No native timber used - Elemental chlorine free

Basic properties	ISO						
Basis Weight	(ISO 536)	(g/m <sup>2</sup> )	57	60	65	70	75
Thickness	(ISO 534)	(µm)	52	55	60	65	70
Bulk	(ISO 534)	(cm <sup>3</sup> /g)	0.92	0.92	0.92	0.93	0.93
Brightness D65	(ISO 2470)	(%)	80	82	85	85	85
L-value D65	(ISO 5631-2)	(D65/10°)	88	89	90	90	90
a-value D65	(ISO 5631-2)	(D65/10°)	0.6	0.6	0.6	0.6	0.6
b-value D65	(ISO 5631-2)	(D65/10°)	-5.5	-5.5	-5.5	-5.5	-5.5
Opacity.	(ISO 2471)	(%)	92	93	93	94	95
Gloss Hunter	(ISO 8254-1)	(%)	53	54	55	55	55

PRODUCT FAMILY:  
Vantage LWC

FINISH:  
Gloss

Norske Skog Boyer is certified according to:

PRINTING METHOD:  
Heat set web offset

PRODUCER:  
Boyer

Paper Profile Document  
AS/ANZ ISO 14001:2015  
FSC Forest Management  
FSC Chain of Custody  
PEFC Chain of Custody

*Last Updated:  
29 September 2016*

## We use cookies

Norske Skog ASA This website uses cookies to track your behavior and to improve your experience on the site. [norskeskog.com](http://norskeskog.com)  
You can always delete saved cookies by visiting the advanced settings of your browser. [Read more about our cookies.](#)

Do not accept cookies

Only accept functional cookies

Accept all cookies