

Boyer Vantage LWC

End use: Magazines, catalogues, supplements, direct mail, inserts/flyers

- 100% plantation softwood fibre - All fibre is sourced from well managed plantation forests and other controlled sources - No native timber used - Elemental chlorine free

Basic properties	ISO						
Basis Weight	(ISO 536)	(g/m ²)	51	54	57	60	65
Thickness	(ISO 534)	(µm)	52	54	56	58	61
Bulk	(ISO 534)	(cm ³ /g)	1.02	1.0	0.98	0.96	0.94
Brightness D65	(ISO 2470)	(%)	73	73	73	73	73
L-value D65	(ISO 5631-2)	(D65/10°)	87	87	87	87	87
a-value D65	(ISO 5631-2)	(D65/10°)	0.2	0.2	0.2	0.2	0.2
b-value D65	(ISO 5631-2)	(D65/10°)	-0.5	-0.5	-0.5	-0.5	-0.5
Opacity.	(ISO 2471)	(%)	91	92	93	94	95
Gloss Hunter	(ISO 8254-1)	(%)	43	43	45	45	45

PRODUCT FAMILY:
Vantage Super

FINISH:
Gloss

PRINTING METHOD:
Heat set web offset

PRODUCER:
Boyer

Last Updated:
29 September 2016

Norske Skog Boyer is
certified according to:

Paper Profile Document
AS/ANZ ISO 14001:2015
FSC Forest Management
FSC Chain of Custody
PEFC Chain of Custody

We use cookies

Norske Skog ASA This website uses cookies to track your behavior and to improve your experience on the site. norskeskog.com
You can always delete saved cookies by visiting the advanced settings of your browser. [Read more about our cookies.](#)

Do not accept cookies

Only accept functional cookies

Accept all cookies