

Boyer Vantage LWC

Utilización final: Magazines, catalogues, supplements, direct mail, inserts/flyers

- 100% plantation softwood fibre - All fibre is sourced from well managed plantation forests and other controlled sources - No native timber used - Elemental chlorine free

Propiedad	ISO							
Gramaje	(ISO 536)	(g/m ²)	51	54	57	60	65	
Espesor	(ISO 534)	(µm)	52	54	56	58	61	
Volumen Específico	(ISO 534)	(cm ³ /g)	1.02	1.0	0.98	0.96	0.94	
Blancura D 65	(ISO 2470)	(%)	73	73	73	73	73	
Tonalidad L D 65	(ISO 5631-2)	(D65/10°)	87	87	87	87	87	
Tonalidad A D 65	(ISO 5631-2)	(D65/10°)	0.2	0.2	0.2	0.2	0.2	
Tonalidad B D 65	(ISO 5631-2)	(D65/10°)	-0.5	-0.5	-0.5	-0.5	-0.5	
Opacidad	(ISO 2471)	(%)	91	92	93	94	95	
Brillo (Hunter)	(ISO 8254-1)	(%)	43	43	45	45	45	

FAMILIA DE PRODUCTOS:
Vantage Super

SISTEMA DE IMPRESIÓN:
Heat set web offset

*Last Updated:
29 September 2016*

ACABADO:
Gloss

PRODUCTOR:
Boyer

Norske Skog Boyer
tiene la certificación:

Paper Profile Document
AS/ANZ ISO 14001:2015
FSC Forest Management
FSC Chain of Custody
PEFC Chain of Custody