

Boyer Vantage LWC

Anwendung: Magazines, catalogues, supplements, direct mail, inserts/flyers

- 100% plantation softwood fibre - All fibre is sourced from well managed plantation forests and other controlled sources - No native timber used - Elemental chlorine free

Grundlegende Merkmale	ISO						
Flächenbezogene Masse	(ISO 536)	(g/m ²)	51	54	57	60	65
Dicke	(ISO 534)	(µm)	52	54	56	58	61
Spez. Volumen	(ISO 534)	(cm ³ /g)	1.02	1.0	0.98	0.96	0.94
Weisse, D65/10 (UV)	(ISO 2470)	(%)	73	73	73	73	73
L*	(ISO 5631-2)	(D65/10°)	87	87	87	87	87
a*	(ISO 5631-2)	(D65/10°)	0.2	0.2	0.2	0.2	0.2
b*	(ISO 5631-2)	(D65/10°)	-0.5	-0.5	-0.5	-0.5	-0.5
Opazität	(ISO 2471)	(%)	91	92	93	94	95
Glanz (Hunter)	(ISO 8254-1)	(%)	43	43	45	45	45

PRODUKTFAMILIE:
Vantage Super

OBERFLÄCHE:
Gloss

DRUCKVERFAHREN:
Heat set web offset

HERSTELLER:
Boyer

*Last Updated:
29 September 2016*

Norske Skog Boyer ist
zertifiziert nach:

Paper Profile Document
AS/ANZ ISO 14001:2015
FSC Forest Management
FSC Chain of Custody
PEFC Chain of Custody