

# Boyer Vantage LWC

**Anwendung:** Magazines, catalogues, supplements, direct mail, inserts/flyers

- 100% plantation softwood fibre - All fibre is sourced from well managed plantation forests and other controlled sources - No native timber used - Elemental chlorine free

Grundlegende Merkmale	ISO							
Flächenbezogene Masse	(ISO 536)	(g/m <sup>2</sup> )	51	54	57	60	65	
Dicke	(ISO 534)	(µm)	52	54	56	58	61	
Spez. Volumen	(ISO 534)	(cm <sup>3</sup> /g)	1.02	1.0	0.98	0.96	0.94	
Weisse, D65/10 (UV)	(ISO 2470)	(%)	73	73	73	73	73	
L*	(ISO 5631-2)	(D65/10°)	87	87	87	87	87	
a*	(ISO 5631-2)	(D65/10°)	0.2	0.2	0.2	0.2	0.2	
b*	(ISO 5631-2)	(D65/10°)	-0.5	-0.5	-0.5	-0.5	-0.5	
Opazität	(ISO 2471)	(%)	91	92	93	94	95	
Glanz (Hunter)	(ISO 8254-1)	(%)	43	43	45	45	45	

PRODUKTFAMILIE:  
Vantage Super

OBERFLÄCHE:  
Gloss

DRUCKVERFAHREN:  
Heat set web offset

HERSTELLER:  
Boyer

*Last Updated:*  
29 September 2016

Norske Skog Boyer ist  
zertifiziert nach:

Paper Profile Document  
AS/ANZ ISO 14001:2015  
FSC Forest Management  
FSC Chain of Custody  
PEFC Chain of Custody