

# Saugbrugs NorSC Lite

**Utilisation finale:** Magazines, inserts, catalogues, direct mail and door drop.

**Product Family:** SC

Caractéristiques de base	ISO								
Grammage	(ISO 536)	(g/m <sup>2</sup> )	37	39	42	45	47.4	52	56
Epaisseur	(ISO 534)	(µm)	39	43	44	45	46	48	49
Densité	(ISO 534)	(kg/m <sup>3</sup> )	950	960	980	1015	1030	1130	1140
Main	(ISO 534)	(cm <sup>3</sup> /g)	1.05	1.04	1.03	1.01	0.97	0.88	0.88
Blancheur D65	(ISO 2470)	(%)	69	69	69	69	69	69	69
Blancheur CIE	(ISO 11475)	(%)	52	52	52	52	52	52	52
Luminance	(ISO 5631-2)	(D65/10°)	88	88	88	88	88	88	88
Valeur A	(ISO 5631-2)	(D65/10°)	-1.4	-1.4	-1.4	-1.4	-1.4	-1.4	-1.4
Valeur B	(ISO 5631-2)	(D65/10°)	4.3	4.3	4.3	4.3	4.3	4.3	4.3
Opacité	(ISO 2471)	(%)	87	88	89	90	91	93	94
Brillance Hunter	(ISO 8254-1)	(%)	36	37	40	42	44	45	46
Lissé ( Rugosité ) PPS 10	(ISO 8791-4)	(µm)	1.3	1.3	1.3	1.2	1.2	1.1	1.1

FAMILLE DE  
PRODUITS:  
Nor

MÉTHODE  
D'IMPRESSON:  
Heatset & Rotogravure

CHARACTERIZATION  
DATA:  
Fogra 40

*Last Updated:  
May 2019*

SURFACE:  
Gloss

PRODUCTEUR:  
Saugbrugs

**Norske Skog  
Saugbrugs est certifié  
selon:**

Paper Profile  
PEFC  
FSC  
EU Timber Regulation  
ISO 50001: 2018  
ISO 9001: 2015  
ISO 14001: 2015  
EU Ecolabel  
click here to see a few of our  
customers who are currently  
benefiting from Norsc Lite  
Norske Skog Saugbrugs -  
Carbon Footprint