

Saugbrugs NorSC Lite

Anwendung: Magazines, inserts, catalogues, direct mail and door drop.

Product Family: SC

Grundlegende Merkmale	ISO								
Flächenbezogene Masse	(ISO 536)	(g/m ²)	37	39	42	45	47.4	52	56
Dicke	(ISO 534)	(µm)	39	43	44	45	46	48	49
Blattdichte	(ISO 534)	(kg/m ³)	950	960	980	1015	1030	1130	1140
Spez. Volumen	(ISO 534)	(cm ³ /g)	1.05	1.04	1.03	1.01	0.97	0.88	0.88
Weisse, D65/10 (UV)	(ISO 2470)	(%)	69	69	69	69	69	69	69
Weisse CIE	(ISO 11475)	(%)	52	52	52	52	52	52	52
L*	(ISO 5631-2)	(D65/10°)	88	88	88	88	88	88	88
a*	(ISO 5631-2)	(D65/10°)	-1.4	-1.4	-1.4	-1.4	-1.4	-1.4	-1.4
b*	(ISO 5631-2)	(D65/10°)	4.3	4.3	4.3	4.3	4.3	4.3	4.3
Opazität	(ISO 2471)	(%)	87	88	89	90	91	93	94
Glanz (Hunter)	(ISO 8254-1)	(%)	36	37	40	42	44	45	46
Glätte	(ISO 8791-4)	(µm)	1.3	1.3	1.3	1.2	1.2	1.1	1.1

PRODUKTFAMILIE:
Nor

OBERFLÄCHE:
Gloss

DRUCKVERFAHREN:
Heatset & Rotogravure

HERSTELLER:
Saugbrugs

CHARACTERIZATION
DATA:
Fogra 40

*Last Updated:
May 2019*

Norske Skog
Saugbrugs ist
zertifiziert nach:

Paper Profile
PEFC
FSC
EU Timber Regulation
ISO 50001: 2018
ISO 9001: 2015
ISO 14001: 2015
EU Ecolabel
click here to see a few of our
customers who are currently
benefiting from Norsc Lite
Norske Skog Saugbrugs -
Carbon Footprint